

ADITIVO DINAS

Product used in the formulation of dyes solution, indicated for application in the film as a treatment indicator. Used as a way to guarantee the fixation of the ink on the film.

CODE: 022391-00

BASIC PROPERTIES

Product type..... Substance

Aspect..... Colorless Liquid

APPLICATION INSTRUCTIONS

Cut a piece of the film that you want to assess the level of treatment;

Dip the swab in the said solution and apply it on the substrate, uniformly, from one end of the film to the other, in the transverse direction of embobing;

After applying the product, check that the solution wire remains unchanged for 3 (three) seconds. If the solution thread does not change, it means that the treatment level of the substrate is the same as that of the applied solution. If the yarn changes, apply a lower value solution in dynes/cm.

SAFETY RECOMMENDATION

Store the product in sheltered, ventilated environments.

Flammable product, keep away from sparks, sources of ignition, do not smoke.

Product when applied emanates vapors that should be avoided with the correct use of PPE, such as masks and respirators.

Avoid skin contact using gloves, goggles, proper clothing, protective creams etc.

ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - Km 336 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48)3461-8000 Fax: (48) 3461-8001

www.anjo.com.br



TECHNICAL DATA SHEET

FR413 (REV. 01)

Keep away from contact with children and animals.

STATUTORY REQUIREMENTS

ANVISA (Brazilian Health Regulatory Agency): Rules heavy metal levels for food packaging that may have contact with children;

FDA (Food and Drug Administration): Norm american regulating foods and drugs for toxicity;

ABRE (Associação Brasileira de Embalagens): Exclusion list to toxicity to inkd and solvente the print;

EUPIA (European Printing Ink Association): European exclusion list per toxicity in inks and solvent for printing.

OBSERVATION

The instructions in this bulletin are based on our experience and technical knowledge, however, some factors are independent of our control as a manufacturer, such as:

substrate treatment, application, working conditions, and so forth. Due to substrate diversity and printing conditions, this sheet is sent for proposed information and is offered without warranty as it must be confirmed by industrial testing before products are used.

Use of thinner other than specified may affect product performance.

Anjo is constantly making improvements to its products and we reserve the right to change the contents of this technical bulletin without prior notice. Anjo is not responsible for improper use of the product.

ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - Km 336 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48)3461-8000 Fax: (48) 3461-8001

www.anjo.com.br



TECHNICAL DATA SHEET

FR413 (REV. 01)

Shelf life 6 months

Packing

Bottle.....0,1Kg

Metal bucket.....16Kg

Review 28/07/2020

ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - Km 336 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48)3461-8000 Fax: (48) 3461-8001

www.anjo.com.br